



WR Ridge-former



www.struikholland.nl

Struik WR Ridge-former

The WR Ridge-former is non-driven machine that especially is designed for ridging light to medium density soil, with or without stones.





The ridge former is standard executed with wear-resistant spring tines and ridgers mounted on vibro-springs. These ridgers create the first small row and the ridging hood forms the final ridges.

The WR ridge-former is available in sizes ranging from 2x75 cm to 8x90 cm.

Strenghts:

- Solid construction
- Easy adjustment
- Ridging hood with removable cover plates for ridging in emerging crops
- Bed former possible
- Rigid or foldable frame available
- Several options available



Type				
2WR165 2x75cm	1500	50hp/36kW	2x75cm	740
4WR320 4x75cm	3000	80hp/58kW	4x75cm	850
4WR380 4x90cm / 36"	3600	85hp/62kW	4x90cm/36"	1150
6WR465 6x75cm	4500	120hp/88kW	6x75cm	1400
6WR555 6x90cm / 36"	5400	125hp/91kW	6x90cm/36"	1700
8WR610 8x75cm	5500	140hp/110kW	8x75cm	1950
8WR742 8x90cm / 36"	6100	140hp/110kW	8x90cm/8x36"	2100

Struik Wieringermeer B.V. / Export B.V.

Schelphorst 67
 1771 SM WIERINGERWERF
 The Netherlands
 Tel. +31 (0) 227-603144
 www.struikholland.nl