





Optional: adjustable ridging point



Optional: crop protection shaft



Optional: crop protection shaft

Highlights ZF

- Cultivation and weed control with a single machine
- Can be used for various crops
- Available for 2 to 8 rows
- Adjustable tilling units for use with crops of differing row distances
- Shear bolt protection on every tilling unit
- As the tilling units are driven individually, there is clearance between the tilling elements, both laterally and upwards. This makes it possible to till in crops with high leaf content
- The tilling elements are fitted with 8 hooks as standard. Optional narrow elements are available with 4 hooks so that tilling can take place without affecting the crop's root system.
- Crop protection shaft, adjustable from 95 to 170 mm (optional)
- Available with widia hooks (optional)
- Gearboxes of 100 hp and 300 hp

Type	 min.				 kg
2ZF75	65hp/48kW	1500	4x75cm/4x30"	1000	800
2ZF90	70hp/52kW	1800	4x90cm/4x36"	1000	850
4ZF75	100hp/73kW	3000	4x75cm/4x30"	1000	1300
4ZF90	100hp/73kW	3600	4x90cm/4x36"	1000	1400
6ZF75	140hp/103kW	4500	6x75cm/6x30"	1000	2650
6ZF90	140hp/103kW	5400	6x90cm/6x36"	1000	2750
8ZF75	170hp/125kW	6000	8x75cm/8x30"	1000	2900
8ZF90	170hp/125kW	7200	8x90cm/8x36"	1000	3000

Struik Wieringermeer B.V. - Export B.V.
 Bedrijventerrein Robbenplaat 5000-6000
 Schelphorst 67/32
 1771 SM Wieringerwerf
 The Netherlands

Tel. +31(0)227-603144
 E-mail: struik@struikholland.nl
 Website: www.struikholland.nl

Dealer: